

Dirt Doctor Field Groomer



Quality Built - Made in U.S.A.

SPECIFICATIONS

Dirt Doctor 4' with tow package	Part #10003306	\$4,075.00
4' with 3-point hitch	Part #10003307	3,599.00
4' Brush attachment	Part #10003334	add 269.00
6' with tow package	Part #10003308	4,525.00
6' with 3-point hitch	Part #10003309	4,065.00
6' Brush attachment	Part #10003335	add 345.00

DIMENSIONS:

4' model, 3 pt. hitch:	56"w x 56"l x 37"h	Grooming path:	48" width
6' model, 3 pt. hitch:	80"w x 56"l x 37"h	Grooming path:	72" width
4' model, tow pkg	69"w x 100"l x 55"h	37" h with wheels up	
6' model, tow pkg	93"w x 100"l x 55"h	37" h with wheels up	
Min. tongue height:	9"		
Optional broom kit:	Add 14" to length		

SHIP WEIGHT:

4' model, 3 pt. Hitch	886 lbs.	with Tow package	1,024 lbs
6' model, 3 pt. Hitch	1,154 lbs	with Tow package	1,294 lbs
Common Carrier F.O.B., Aurora CO 80011			

Requirements:

Minimum Tractor Type: Compact Utility Horsepower: 25 hp or greater. Lug tires recommended.

Note: Units can not be pulled with standard Lawn & Garden type tractors or Gator type utility vehicles.

Construction:

All welded structural steel, industrial grade beatings with grease fittings and bearings, 3/4" hitch pins and 7/8" lift pins.

Visit our website at www.whitlampaint.com
or call us toll free at 1-800-321-8358

Terms: Net 30 Days to approved accounts

F.O.B.: Manufacturing Plant

We accept most major credit cards:



October 2006

WHITLAM
PAINT COMPANY
QUALITY COATINGS SINCE 1900

Dirt Doctor Field Groomer

SPECIFICATIONS

- Harrow Teeth:** 4' model: 13 - 1.75" w x 10" long reversible teeth.
6' model: 20 - 1.75" w x 10" long reversible teeth.
- Harrow Bar:** Quick-change, 3-position depth adjustment.
- Weight Tray:** 49"w x 16"l x 1.5" deep, expanded metal base for drainage.
- Pulverizing Bar:** 4' model, consists of 28 - 5.5" diameter, 8 tooth, pulverizing discs.
6' model, consists of 40 - 5.5" diameter, 8 tooth, pulverizing discs.
3-position, ride-height adjustment
- Center Drag Grate:** 48"w x 16"l, 3 in. metal grating with 1.5" x 3" openings. Adjustable height.
- Compacting Roller:** 12" diameter, All steel roller with flip over scraper blade to keep drum clean.
- Lift Jack:** Industrial grade, trailer type with 6" pneumatic caster.
Quick disconnect allows caster to be easily removed when drag is in use.
- Warranty:** 18-month materials and workmanship.
- OPTIONS:**
- Tow Package:** 4.80-8 road-rated pneumatic tires on 8" x 3.54" wheels.
Note: Not intended for high-speed transportation. Tow package is for transport between fields only.
- Broom Kit:** Synthetic fiber, replaceable broom segments. Raise and lower with spring latch.



Brush attachment



3-point hitch

Terms: Net 30 Days to approved accounts
F.O.B.: Manufacturing Plant
We accept most major credit cards:



October 2006

Visit our website at www.whitlampa.com
or call us toll free at **1-800-321-8358**

WHITLAM
PAINT COMPANY
QUALITY COATINGS SINCE 1900